

Package: sjtable2df (via r-universe)

September 4, 2024

Title Convert 'sjPlot' HTML-Tables to R 'data.frame'

Version 0.0.3

Description A small set of helper functions to convert 'sjPlot'
HTML-tables to R data.frame objects / knitr::kable-tables.

License GPL (>= 3)

URL <https://github.com/kapsner/sjtable2df>

BugReports <https://github.com/kapsner/sjtable2df/issues>

Depends R (>= 2.10)

Imports data.table, kableExtra, magrittr, rlang, rvest, stats, xml2

Suggests knitr, lintr, lme4, mlbench, rmarkdown, sjPlot, testthat (>=
3.0.1)

VignetteBuilder knitr

Date/Publication 2023-04-13 15:11:57 UTC

Encoding UTF-8

RoxygenNote 7.2.3

Repository <https://kapsner.r-universe.dev>

RemoteUrl <https://github.com/kapsner/sjtable2df>

RemoteRef HEAD

RemoteSha 3ad71ef2745eda99af6e1107b2d454245dc6bf60

Contents

mtab2df	2
xtab2df	3

Index	5
--------------	----------

 mtab2df

mtab2df

Description

Convert table from ‘sjPlot::tab_model’ to R data.frame or ‘knitr::kable’

Usage

```
mtab2df(mtab, n_models, output = "data.table", ...)
```

Arguments

mtab	A model table, created with ‘sjPlot::tab_model’.
n_models	An integer, specifying the number of models in the table.
output	A character vector. Allowed values are: "data.table" (default), "data.frame" or "kable". The function’s return value is of the respective type.
...	Further arguments to be passed to ‘kableExtra::kbl’.

Value

The table is returned as an R object of the type specified with the ‘output’ argument.

Examples

```
set.seed(1)
dataset <- data.table::data.table(
  "var1" = factor(sample(
    x = c("yes", "no"),
    size = 100,
    replace = TRUE,
    prob = c(.3, .7)
  )),
  "var2" = factor(sample(
    x = c("yes", "no"),
    size = 100,
    replace = TRUE
  )),
  "var3" = rnorm(100)
)

# models
m0 <- stats::glm(
  var1 ~ 1,
  data = dataset,
  family = binomial(link = "logit")
)
m1 <- stats::glm(
```

```

    var1 ~ var2,
    data = dataset,
    family = binomial(link = "logit")
  )
m2 <- stats::glm(
  var1 ~ var2 + var3,
  data = dataset,
  family = binomial(link = "logit")
)

m_table <- sjPlot::tab_model(m0, m1, m2, show.aic = TRUE)

final_tab <- sjtable2df::mtab2df(mtab = m_table, n_models = 3)

```

xtab2df

xtab2df

Description

Convert table from 'sjPlot::tab_xtab' to R data.frame or 'knitr::kable'

Usage

```
xtab2df(xtab, output = "data.table", threeparttable = FALSE, ...)
```

Arguments

xtab	A contingency table, created with 'sjPlot::tab_xtab'.
output	A character vector. Allowed values are: "data.table" (default), "data.frame" or "kable". The function's return value is of the respective type.
threeparttable	Boolean value indicating if a threeparttable scheme should be used.
...	Further arguments to be passed to 'kableExtra::kbl'.

Value

The table is returned as an R object of the type specified with the 'output' argument.

Examples

```

set.seed(1)
dataset <- data.table::data.table(
  "var1" = sample(
    x = c("yes", "no"),
    size = 100,
    replace = TRUE,
    prob = c(.3, .7)
  ),

```

```
"var2" = sample(
  x = c("yes", "no"),
  size = 100,
  replace = TRUE
)
)

xtab <- sjPlot::tab_xtab(
  var.row = dataset$var1,
  var.col = dataset$var2,
  show.summary = TRUE,
  use.viewer = FALSE
)

sjtable2df::xtab2df(xtab = xtab)
```

Index

mtab2df, 2

xtab2df, 3